


[Web](#) [Images](#) [Groups](#) [News](#) [Froogle](#) [Local](#)^{New!} [more »](#)

per instance attributes

Search

[Advanced Search](#)
[Preferences](#)
WebResults 1 - 10 of about 10,800,000 for **per instance attributes**. (0.31 seconds)Gilles' WebLog : Per instance configuration for Custom Pipeline ...

In fact, to prepare your **per instance** configuration document, ... I did not make the connection between the "vt" **attribute** and the VARTYPE enum and didn't ...

blogs.msdn.com/gzunino/archive/2004/07/16/185842.aspx - 27k - [Cached](#) - [Similar pages](#)

Virtual Method Tables in Python

For each **instance**, there is a set of **per-instance attributes**, whose values will be different in a different **instance** of the same class. ...

www.foretec.com/python/workshops/ 1998-11/proceedings/papers/lowis/lowis.html - 39k - [Cached](#) - [Similar pages](#)

[PS] Virtual Method Tables in Python Martin von Lo'wisHumboldt ...

File Format: Adobe PostScript - [View as Text](#)

Therefore, I record assignments to **instance attributes** in the extra ... This gives a constant overhead of a fewfunction calls **per attribute** lookup. ...

www.foretec.com/python/workshops/ 1998-11/proceedings/papers/lowis/lowis.ps - [Similar pages](#)

Code Generation From UML For Small Systems

Two **instance attributes** (one public, one private), which occur once **per** object (**instance** of the class);. A private class operation, which applies across all ...

www.artisansw.com/news/codegen2.asp - 36k - [Cached](#) - [Similar pages](#)

[Zope-dev] Manipulating Meta-Type Global Add list on per-instance ...

[Zope-dev] Manipulating Meta-Type Global Add list on **per-instance** basis ...

you are "hiding" the class member when you assign to the **instance >attribute**. ...

mail.zope.org/pipermail/zope-dev/2000-March/003549.html - 6k - [Cached](#) - [Similar pages](#)

[Zope-dev] Manipulating Meta-Type Global Add list on per-instance ...

[Zope-dev] Manipulating Meta-Type Global Add list on **per-instance** basis ...

you are "hiding" the class member when you assign to the **instance attribute**. ...

mail.zope.org/pipermail/zope-dev/2000-March/003515.html - 4k - [Cached](#) - [Similar pages](#)

[[More results from mail.zope.org](#)]

blogfour: August 2005 Archives

Add **instance attribute** to submission element, so a submission result can ...

Fix selected **attribute** behaviour for <case> **per** the XForms Errata (bug 302497) ...

www.beaufour.dk/blog-archives/2005/08/ - 16k - [Cached](#) - [Similar pages](#)

Code Footprint Reduction Techniques

A simple static structure can store **per-class attributes**, ... For **instance**, this switch statement, taken from nsHTMLContentSink is really just a massive ...

www.mozilla.org/performance/ footprint-reduction-techniques.html - 19k - [Cached](#) - [Similar pages](#)

PGL: Object and Instance Attributes

... their parent objects, but these values may be overridden on a **per-attribute** basis. The complete list of object and **instance attributes** is given below. ...

www.icase.edu/reports/interim/29/PGL/Attributes.html - 10k - [Cached](#) - [Similar pages](#)

Submit

A node from the **instance** data is selected, based on **attributes** on the submission element. The indicated node and all nodes for which it is an ancestor are ...

www.w3.org/TR/2005/PER-xforms-20051006/slice11.html - 27k - [Cached](#) - [Similar pages](#)